

4MSX , 4CSX

อุปกรณ์แบ่งภาพหน้าจอ 4 Channels



SPECIFICATION

Model	4 MSX (B/W)	4 CSX (COLOR)
Picture Refresh Rate	CCIR : 25 Field/Sec. EIA : 30 Field/Sec.	PAL : 25 Field/Sec. EIA : 30 Field/Sec.
Digital Memory	1024 x 512 Full Screen	1024 x 512 Full Screen
Horizontal Resolution	700 pixels Minimum, Full Screen	-
Digital Quality	8 bits (256 grey scale)	-
Video Format	EIA or CCIR - Monochrome Video Signal	PAL Color Video Signal
Video Input	BNC x 4, 2:1 Interlace Composite Video 1.0Vp-p, 75 Ω	BNC x 5, 4-CH Camera Input, 1VCR Input,
Video Output	BNC x 2, Quad Video Output & Switching Video Output	BNC x2,1 Monitor Output, 1 VCR Output,1Vp-p 75 Ω
Video output format	Full Screen, QUAD, Auto Switch	Full Screen, QUAD, Freeze,PIP, Auto Switch
OSD Menu	-	Yes
Motion Detector	-	Yes
Video Loss Alarm	-	Yes
Alarm Record	-	Startup,loss and motion
Zoom	-	Yes
Timer	-	Built-in real time clock
Title	-	Up to 8 characters
Picture adjustment	-	Brightness ,Contrast ,Sharpness,Saturation and Hue
Auto Scan Timing	4 seconds	1~99 seconds
Power Supply	12 VDC 200mA	12 VDC 1A
Operation Temperature	-10°C - 50°C	-10°C - 50°C
Dimension / Weight	210(L) x 220 (W) x 44(H) mm/1.4Kg	210(L) x 290 (W) x 44(H) mm/1.6Kg