

Wireless Magnetic Contact

Model : AVA MC

Technical specifications

- ▶ Battery 3.6V , LiMnO2 0.25-0.3 Ah
- ▶ Working frequency 868 Hz (multichannel)
- ▶ Wireless link distance up to 300 m
- ▶ Operating temperature -10 °C to +60 °C
- ▶ Storage temperature -40 °C to +85 °C
- ▶ RF protection 10 V/m in range 80 MHz - 1 GHz
- ▶ EMC protection 8 kV
- ▶ Reed switch 2
- ▶ Working distance 25 mm - 30 mm
- ▶ Anti - tamper switch yes (double protection)
- ▶ Dimensions 93 mm x 31 mm x 27 mm
- ▶ Weight 83.5 gr



Wireless Magnetic Contact + Shock Sensor

Model : AVA MCS

Technical specifications

- ▶ Battery 3.6V , LiMnO2 0.25-0.3 Ah
- ▶ Working frequency 868 Hz (multichannel)
- ▶ Wireless link distance up to 300 m
- ▶ Operating temperature -10 °C to +60 °C
- ▶ Storage temperature -40 °C to +85 °C
- ▶ RF protection 10 V/m in range 80 MHz - 1 GHz
- ▶ EMC protection 8 kV
- ▶ Reed switch 2
- ▶ Working distance 25 mm - 30 mm
- ▶ Anti - tamper switch yes (double protection)
- ▶ Vibration sensor Integrated
- ▶ Dimensions 93 mm x 31 mm x 27 mm
- ▶ Weight 83.5 gr

