

CM1412 (จอสี 14 นิ้ว)

CM2000 (จอสี 20 นิ้ว)

14 " COLOR

20 " COLOR

SPECIFICATION

- ❖ HIGH SHARPNESS > 500 TV LINES
- ❖ VIDEO / BRIGHT / COLOR SELECT
- ❖ SPEAKER POWER OUTPUT SELECT
- ❖ INTERNATIONAL ROUTE PAL / NTSC
- ❖ AFC TIME CONSTANT CONTROL
- ❖ AUDIO OUTPUT 1.2W
- ❖ METAL CRUST
- ❖ BUILT-IN TOILET FILTER
- ❖ TWO COMPOSITE AND Y/C VIDEO INPUT
- ❖ AUTO BRIGHT LIMITER WITH COLOR STABILIZATION

MODEL	CM-1400S (14 " COLOR MONITOR) / CM-2000 (20" COLOR MONITOR)
Power Supply	220-240VAC
Power Consumption	99W
Inputs/Outputs	Video : Inputs : / Outputs : 2)
	1.0V [P-P] compound / 75 1/2 or high resistance circuit
	S-Video (Inputs : 2 / Outputs : 2)
	1.0V [P-P] compound / 75 or high resistance circuit (PAL / NTSC)
	C : 0.3V [P-P] /75 1/2 or high resistance circuit (PAL)
	C : 0.228V [P-P] /75 1/2 or high resistance circuit (NTSC)
	Audio : 4 Inputs (RCA) 4 Outputs (RCA)
Standard	PAL / NTSC / M-NTSC
Horizontal Resolution	500 TV Lines (Level)
Top Vision Gain	41 dB , 3 dB
Scanning Line	< 5%
Scanning Geometric Degree	< 2%
Over Scanning	8%
Picture Size (about)	51 cm (20 ") diagonal line (CM2000)
CRT size (about)	55cm (21-5/8 ") diagonal line (CM2000)
19 " machine installation	no
Operating Temperature	-14 F to +122 F (-10C to +50C)
Operarying humidity	< 90%
Speaker output	3W (-8dB)
Size (width x height x depth)	500 x 474 x 500 mm. (CM2000)
Weight	1058.2 oz./30kg (CM2000 / not including the outer box)