

IP CAMERA FULL HD

Full HD 1920x1080 Video @30fps Optical ZOOM 10x A/F

MODEL : CMNC-200



[Features]

- 2.0 Megapixel 1/2.5" CMOS Image sensor
- Max full HD(1920x1080@30fps) video with progressive scan
- Optical 10x zoom with Auto-focusing
- Live video HDMI interface
- Dual streaming of ultra fine quality H.264/MJPEG or H.264/H.264
- Video Bitrate : 32kbps ~ 8Mbps
- CMS up to 36 channels live monitoring, recording, search&playback
- Sensor input terminals
- 1 channel audio In/Out
- Alarm output terminals
- RS-485 terminals
- SD Card Slot
- PoE optional

[Specifications]

NETWORK	
Interface	Ethernet 10/100Base-T (RJ-45)
Protocol	TCP/IP, UDP, Multicast, DHCP, SMTP, HTTP, SNMP, RTP, RTSP
VIDEO	
Standards	H.264 / MJPEG or H.264 / H.264
AUDIO	
Algorithm	G.711u AAC
Input	1 x Line-In
Output	1 x Line-Out
Sample Rate	8KHz 32KHz
Bitrate	64Kbps 64Kbps, 128Kbps, 192Kbps
SERIAL PORT	
Sensor Input	1 x RS-485
Data Rate	2,400bps ~ 115,200bps
SENSOR / ALARM / ETC	
Sensor Input	1port
Alarm Output	1port
Reset Button	1port
CAMERA	
Image Sensor	1/2.5" CMOS Image sensor
Lens	1/3.6", f=4.5~45.0mm F1.8~2.2 x10 optical zoom and digital zoom
Output	1x HDMI
Exposure	Flickerless, Metering, Mode, Aperture, Shutter Speed, Brightness
Focus	Focus Range, Zoom Tracking
White Balance	Auto, Indoor, Outdoor
Motion Detection	On/Off
PHYSICAL	
Power Source	DC 12V, PoE(Power over Ethernet) : 802.3af
Power Consumption	Max. 500mA
Operating Temp.	-10°C ~ 50°C / 14°F ~ 122°F
Humidity	30% ~ 80%RH
USER INTERFACE	
System Status	LED
MANAGEMENT SW	Support web viewer, 16ch viewer, 36ch viewer (optional)

[Dimensions]

