

INTELLIGENT AUTOGATE SOLUTION

สะดวก ปลอดภัย ไม่กลัวฝน DARE TO RAINY



www.facebook.com/www.gunkamony



ISO
FC CE



Marantec



POLAND



Specification of motor MO-600

Weight of GATE	600 Kg
Power Supply	220 ~ 240 Vac , 50/60 Hz
Motor Horse Power	0.20 hp
Motor Speed	1250 rpm/min
Output Torque	7 N.m
Opening Speed	10.5 M/Min
Rated Power	150 W
Capacitor	16 uf/ 450V
Lubrication	OLVA 240
Driver Type	Gear wheel 19T
Limit Switch	Magnetic Switch
Type of Duty	Heavy Duty
Temperature	-20°C to +60°C
Noise	< 55dB
Dimensions	260 X 162 X 265 mm.

GERMANY

FREE! REMOTE



Specification of motor COMFORT 830

Weight of GATE	600 Kg
Power Supply	220 ~ 230 Vac , 50/60 Hz
Motor Horse Power	0.40 hp
Motor Speed	1250 rpm/min
Output Torque	7 N.m
Opening Speed	10.8 M/Min
Rated Power	300 W
Power Standby	3.9W
Motor	AC with thermo overload Protection
Weight	12 Kg
Gear	Worm gear with clutch
Switch	RPM Sensor
Temperature	-20°C to +60°C
Noise	< 55dB
Dimensions	230 X 260 X 200 mm.
Remote Frequency	2 CH 833.3 MHz

POLAND



Specification of motor MO-800

Weight of GATE	800 Kg
Power Supply	220 ~ 240 Vac , 50/60 Hz
Motor Horse Power	0.24 hp
Motor Speed	1250 rpm/min
Output Torque	14 N.m
Opening Speed	13.5 M/Min
Rated Power	180 W
Capacitor	16 uf/ 450V
Lubrication	OLVA 240
Driver Type	Gear wheel 24T
Limit Switch	Magnetic Switch
Type of Duty	Heavy Duty
Temperature	-20°C to +60°C
Noise	< 55dB
Dimensions	260 X 162 X 265 mm.

เพื่อหลีกเลี่ยงความวุ่นวาย
นำเข้ามาจากต่างประเทศ
*เต็มเมตร **หนาพิเศษ

Accessories

อุปกรณ์เสริมประตูบานเลื่อน



รีโมทป้องกันการก๊อปปี้จากไปแลนด์

100HT : Remote 1 CH 433.92 MHz , TR 5 mW
100H : Remote 2 CH 433.92 MHz , TR 5 mW



GEAR RACK : Tooth Gear: 80 * LENGTH : 1.05 M.
THICKNESS: 30 mm ** FACE: 17 mm



TAIWAN

ACCESSORIES



Specification of motor GENESIS-600N

Weight of GATE	600 Kg
Power Supply	220 ~ 240 Vac , 50/60 Hz
Motor Horse Power	0.30 hp
Motor Speed	55 rpm/min
Output Torque	16 N.m
Opening Speed	13 M/Min
Rated Power	200 W
Capacitor	16 uf/ 450V
Lubrication	OLVA 240
Driver Type	Gear wheel 24T
Limit Switch	Spring Limit Switch
Type of Duty	Heavy Duty
Temperature	-20C to +50C
Noise	< 58dB
Remote Control Mode	Single Button



TAIWAN

ACCESSORIES



Specification of motor GENESIS-1300F

Weight of GATE	1300 Kg
Power Supply	220 ~ 240 Vac , 50/60 Hz
Motor Power	0.93 hp
Motor Speed	1250 rpm/min
Output Torque	18 N.m
Opening Speed	12 M/Min
Rated Power	700 W
Capacitor	16 uf/ 450V
Lubrication	OLVA 240
Driver Type	Gear wheel 24T
Limit Switch	Magnetic Switch
Type of Duty	Heavy Duty
Temperature	-40C to +70C
Noise	< 57dB
Dimensions	260 X 196 X 260 mm.



TAIWAN

ACCESSORIES



Specification of motor GENESIS-2000F

Weight of GATE	2000 Kg
Power Supply	220 ~ 240 Vac , 50/60 Hz
Motor Horse Power	1.07 hp
Motor Speed	1400 rpm/min
Output Torque	18 N.m
Opening Speed	12 M/Min
Rated Power	800 W
Capacitor	16 uf/ 450V
Current	1.5 - 3 Amp
Motor Weight	19 Kg
Lubrication	OLVA 240
Driver Type	Gear wheel 24T
Limit Switch	Magnetic Switch
Type of Duty	Heavy Duty
Temperature	-40C to +80C
Noise	< 60dB
Dimensions	315 X 250 X 355 mm.

UL
CE



ST-680Y : 12 Vdc /150-300 mA
90Flashes/min ABS resin base ,
polycarbonate/acrylic lens
Base Colour : Black Lens Colours : AMBER

CE



ST-01A : 220 Vac 50/60 Hz
With Flash PCB : NO,
ABS resin base , polycarbonate/acrylic lens
Base Colour : Black Lens Colours : AMBER

CE



ST-01B : 220 Vac 50/60 Hz
With Flash PCB : YES (with PCB) ,
ABS resin base , polycarbonate/acrylic lens
Base Colour : Black Lens Colours : AMBER

CE



PHOTO BEAM : Single Infraed Beam
12-24Vdc , Rang 20M.
Relay Output : 1A max 36V



ACCESSORIES



K207DS Control Box 100H Photo Beam ST-680Y

ประตูบานสวิง



Specification of Swing Gate MO 1800F

Power supply	AC 220V ± 10% , 50Hz
Rated power	180W
Rated / max thrust	1800N / 3000N (adjustable)
Opening/Closing time	18 sec
Opening angle	From 90° to 105°
Max leaf weight	280 kg
Max leaf length	3 m
Weather conditions	Rain-Proof



Specification of Swing Gate COMFORT-520

Power Supply	220-230Vac 50Hz
Stroomopname	1 A
Trek-en drukkracht	1500 N
Loopsnellheid	19mm/sec.
Openingstijd	20-30 Sec.
Bewegingsslag	478 mm
Temperature	-20°C to +60°C



ประตูบานเลื่อนอัตโนมัติ

Specification of Auto DOOR บานเดี่ยวและบานคู่

Power Supply	220Vac 50/60 Hz
Controller	Micro Computer Controller
Gear Motor	24 Vdc 300 rpm/min (16:1)
Opening Speed	550 mm – 900 mm/Sec.
Closing Speed	400 mm – 600 mm/Sec.
Hold Open time	0 ~ 10 Sec.
Max. Door Weight	2* 130-160 Kg.
Ambient Temp	-20°C to +50°C



Specification of Barrier BR-535

Power Supply	220Vac
Motor	Single Phase
Input Current	1.8A
Input Power	400W
Revolution	1400 rpm/min
Thermal Protection	120 °C
Torque	120 N.m
Weight	70 Kg.
Max.Continuous Operation	20 °C 260 Cycles
Opening time	3.5 sec.
Streight arm length	3-5 M
Folding arm length	< 4.5M
Fencing arm length	< 4M
Output Voltage for ext. device	12 Vdc , 24Vdc
Protection Fuse	5A
Operating temperature	-20°C to +60°C

TEL: 02-9355761-64
FAX: 02-9355760
E-mail: sales@gunkamoey.com



WWW.RUAFIFA.COM
WWW.GUNKAMOY.COM
facebook.com/www.gunkamoey

บริษัท สمارท อินเตอร์เทรด กรุ๊ป จำกัด SMART INTERTRADE GROUP COMPANY LIMITED

171/98-99 ซอยลาดพร้าว80 (จันทิมา) ถนนลาดพร้าว แขวงวังทองหลาง เขตวังทองหลาง กรุงเทพฯ 10310
171/98-99 SOI LADPRAOW80 LADPRAOW RD. WANGTHONGLANG BANGKOK, THAILAND 10310



ACCESSORIES

VDS-2001 : Loop 1 CH
VDS-2002 : Loop 2 CH