

WIRELESS Control Panel

Model : CP

Technical specifications

CRC16, GFSK Modulation;
Frequency 4 channels in the 868 MHz
ISM band; Bi-directional connection
with all devices; Unique numbers for
devices in the set; Distance up to 300m
outdoor and 50 -100m indoor Permanent
radio monitoring; Radio Test mode for devices;
Simple procedures for set configuration add and remove of devices;
Intuitive procedure for programming system and device's parameters;
Built-in LCD keyboard; Code Hopping Encoding/ Decoding with 64-bit
Encryption/ Decryption key;



Arming, Disarming and programming

16 User codes;
6 functions for Arming;
6 functions for Disarming;
6 groups of detectors;
4 programmable outputs PGM;
Up to 22 devices in the set;
2 inputs for 4 wired detectors;
Event memory capacity: 256 events with date and time;
Built-in siren.

Compatible products

P-Rex , TITAN AG	- Wireless PIR detector
AVA MC , AVA MCS	- Wireless magnetic contact (MCS With Shock Sensor)
AVA RC	- Remote control
AVA FD	- Wireless Fire&Smoke detector
CPC	- Digital communicator
AVA Keypad	- Wireless LCD keypad
SR 200RLi	- Wireless outdoor siren
SP-500	- SIREN เตือนภัย