



■ HD-601

ตรวจจับอุณหภูมิภายในห้อง

- ◆ Rate- of - Rise and Fixed Temperature
- ◆ One - Circuit , Normally Open
- ◆ with mounting plate and terminals



FEATURES

- ◆ Heat detectors are not life safety devices : use for property protection Only Where life safety is required. Smoke detectors must also be used.
- ◆ Battery back-up : heat detectors should be electronically supervised with battery backup at the panel.
- ◆ The rate – of – rise mechanism may be subject to reduced sensitivity over time. Annual testing of the rate – of – rise operation is recommended
- ◆ Refer to NFPA standard 72 for application requirements. Testing and maintenance.

SPECIFICATION

- ◆ **Description** : Rate-of-Rixe and Fixed Temp.,135°F (57°C)
- ◆ **Application** : Normal temperature fluctuations and ceiling Temperatures not Exceeding 100°F (38°C)
- ◆ **Maximum Spacing** : UL Listed 50x50 ft.
- ◆ **Allowance** : FM Approved 30x30 ft.

ELECTRICAL RATINGS

- ◆ 6-125 Volts AC, 3.0 Amp.
- ◆ 6-28 Volts DC, 1.0 Amp.
- ◆ 125 Volts DC, 0.3 Amp.
- ◆ 250 Volts DC, 0.1 Amp.

