

IDVR-16 , IDVR-9



Model	IDVR-16	IDVR-9
Video format	NTSC/EIA or PAL/CCIR	
Hard disk storage	IDE type, UDMA 66, supported over 250 GB HDD	
Record mode	Manual / Alarm / Timer / Motion	
Camera Input Signal	Composite video signal 1 Vp-p 75Ω BNC, 16 channels	Composite video signal 1 Vp-p 75Ω BNC, 9 channels
Camera Loop Back	Composite video signal 1 Vp-p 75Ω BNC, 16 channels	Composite video signal 1 Vp-p 75Ω BNC, 9 channels
Refresh Rate	72 images/sec. for NTSC 60 images/sec. for PAL	120 images/sec. for NTSC 100 images/sec. for PAL
Recording Rate	25 images/sec. for NTSC 18 images/sec. for PAL	25 images/sec. for NTSC 18 images/sec. for PAL
Main Monitor Output	Composite video signal 1 Vp-p 75Ω BNC	
Call Monitor Output	Composite video signal 1 Vp-p 75Ω BNC	
Audio input	4 audio inputs, (RCA)	
Audio output	2 audio outputs, (RCA)	
Video Loss Detection	Yes	
Picture in Picture	Yes (Movable)	
Key Lock	Yes	
Dwell time	Programmable (1-10 Sec)	
Motion Detect Area	15 x 12 targets per camera (NTSC) / 15 x 14 targets per camera (PAL)	
Motion detect sensitivity	256 Levels	
Picture Zoom	2 x 2 (Movable)	
Camera Title	6 letters	
Alarm Output	COM/NO	
Alarm Input	TTL input, Hi (5V), Low (GND)	
Video Adjustable	Color/ Contrast/ Brightness Adjustable	
Remote Control	RS-232 or RS-485	
Time Display Format	YY/MM/DD, DD/MM/YY, MM/DD/YY, OFF	
Power Source	AC100 ~ 240V ±10% switching adaptor	
Operation Temperature	10 ~ 40 °C	
Power Consumption	< 45W	< 32W
Net Weight	5.7 kgs	5.4 kgs
Dimension (mm)	432(W) x 110(H) x 325(D)	430(W) x 300(H) x 65(D)