



IDVR4TFT , IDVR8TFT



JPEG2000

With Built-in 15" TFT LCD

MODEL: IDVR4TFT - IDVR8TFT

Key Features

Superior Picture Quality in Playback : No Mosaic Effect



JPEG2000



MPEG4/JPEG



Space Saving

Stylish & Slim Size



Triplex Operation

Playback/Record/Ethernet



Easy Installation

No Extra Appliances for LCD Monitor



Real Time Live Display

in All Channels



Recording Rate (NTSC/PAL)

In Total

Up to 480 (400)ips



Wall Mountable/Desktop

Wall Mounting Bracket

Various User Interface

Wall-Mounting Bracket



Specification

Contents		IDVR4TFT	IDVR8TFT
Channel		4CH	8CH
Algorithm		JPEG2000	
Recording Rate	720x240 (720x288)	60 (50) ips	120 (100) ips
	360x240 (350x288)	120 (100) ips	240 (200) ips
	360x120 (360x144)	240 (200) ips	480 (400) ips
Simplex/Duplex/Triplex	Triplex		
Compression Rate	5 step select (Basic,Normal,Enhanced,Fine,Super Fine)		
Recording Mode	Schedule (Time , Motion < Alarm) Holiday		
Resolution (NTSC/PAL)	Full (720x240/720x288) / Dual(360x240/360x288) / Quad(360x120/360x144)		
Multi-Language	English, Spanish , French , Italian (To be added more)		
Backup	USB , Download via IP Network, VCR		
TCP/IP (Ethernet)	Remote Monitoring and Download using Remote Viewer Websolution (DDNS) : View,Backup,Play		
Alarm Recording	In : 4/8/16 (NO/NC Selectable) Out : 1 (0.5A Relay Output)		
Motion Detect	Area Division : 16x12 Detection Division : 32x24		
Post Alarm Recording	Duration of Alarm Output : 1~ 300 sec Selectable		
HDD Capacity	1 Up to 400GB		
Storage Structure	Own File System (No FAT , No NTFS)		
Network Interface	RS-232C , RS-485 , Ethernet (TCP/IP)		
Operation	Button , Remote Controller, Operation via RS-232C , TCP/IP		
PTZ Control	RS-485		



The manufacturer reserves the right to change the specification and technical data of device.
The picture may vary from the real product.