



LH SERIES ตรวจก๊าซ

■ LH-85

- MCU processing
- High stability sensor
- Wall Mounted
- Independence Alarm
- AC Power Input
- Auto Reset After Alarm
- Induced Gas: Natural Gas / LPG
- Power Input: AC 220V 50Hz
- Buzzer Level: 70dB/m
- Alarm Density: 15% LEL
- Working Temperature: -10 to +40
- Working Humidity: 90% RH
- Alarm Density Error: +-5% LEL
- Alarm Mode: Flash & Sound Alarm
- Power Consumption: 5W
- Size: 94 * 65 * 42mm



■ LH-86

- MCU processing
- High stability sensor
- Ceiling Mounted
- Independent & Network Option
- Direct Current 12V
- Auto Reset After Alarm
- Detecting Gas: Town Gas.CO
- Working voltage: 12V DC
- Standby Current: 120mA
- Alarm Current: 60mA
- Alarm Density: 50~300PPM
- Buzzer: 70dB(1m)
- Operating Condition: -10 +55 ;
Relative Humidity 90%RH
- Stability: Regular Alarm Density Error +-80PPM
- Repeatability: Repeative Alarm Density Error +-80PPM
- Alarm Density Error: +- 80PPM
- Alarm Mode: Sound&Flash Alarm/Network Alarm Signal
- Size: 115mm x 51mm



■ LH-88

- MCU processing
 - High stability ,energy-saving sensor
 - Wall Mounted
 - Independent & Network Optional
 - Power Input Method Optional
 - Auto Reset After Alarm
 - Induced Gas: Natural Gas
 - Power Input: AC 220V 50Hz
 - Or DC 12V
 - Buzzer Level: 70dB/m
 - Alarm Density: 15% LEL
 - Working Temperature: -10 to + 40
 - Working Humidity: 90% RH
 - Alarm Density Error: +-5% LEL
 - Alarm Mode: Flash & sound alarm /Shut off Gas Valve/
Network Alarm Signal
 - Power Consumed: 5W
 - Size: 120 * 70* 44mm
- Electromagnetic Valve**
- Rated voltage: DC 9V
 - Valve compress: 0.1Mpa
 - Closing time: 1S
 - Closing Method: AC bluse closing
 - Size: 103*64*47mm

