



RACS

0100 0 0010000  
0 0010 001000100  
00100 01  
011 0  
00

# PR602LCD

radius series

*Access Controller and T&A Terminal*



series

**roger**<sup>®</sup>

ROGER ACCESS CONTROL SYSTEM

# roger®



PR 602LCD

## PR602LCD radius series

### Access Controller and T&A Terminal

#### Features:

- Two way, single door access controller
- Standalone or networked operation
- Remote programming from PC\*
- 4000 users with card and/or PIN
- EM 125 kHz cards (EM4100/4102 compatible)
- 127 access groups
- 99 time schedules
- Holiday settings
- Anti-passback
- 32.000 events register
- T&A events registration
- User defined T&A modes
- RS485 interface
- Four lines LCD display
- Operation with external Wiegand, Magstripe or PRT Series reader
- Firmware upgrade through serial port
- Windows XP software
- Indoor/Outdoor installation
- CE

\* communication interface required

## roger®

tel. +48 55 272 01 32

fax +48 55 272 01 33

e-mail: [roger@roger.pl](mailto:roger@roger.pl)

[www.roger.pl](http://www.roger.pl)

All content, specifications and availability subject to change without prior notice.



#### Ordering information

PR602LCD Access Controller and T&A Terminal

#### Technical specification

**Operating voltage** 10-15VDC (recommended linear type power supply unit)

**Current consumption** avg. 100mA

**Tamper** Normally closed contact, 50mA rated

**Reading range** up to 12 cm for ISO type cards (depends on card quality)

**Cards** EM 125 kHz (EM4100/4102 compatible)

**Cable distance to external reader** 150m (500 ft)

**Cable distance between controller and CPR control panel or PC computer** 1200 m (4000 ft)

**Ingress protection** IP65

**Environmental class** Outdoor General, temp. -25°C...+60°C, relative humidity 5-95% (non-condensing)

**Dimensions** 170 X 110 X 42 mm

**Weight** ~ 410g

