



RackCase

เคสติดตั้งอุปกรณ์คอมพิวเตอร์พร้อมระบบ DVR CARD

Model Specifications

VC6116 (4 video inputs)
VC6108A (8 video inputs)
VC6616B (16 video inputs)

Video Input & Image Quality

BNC Video input 1VPP, 75 OHM typical
Proprietary compression (Engine-K)
Resolutions 192x144, 384x288, 768x567
Maximum display 16 cameras 400 fps
Maximum recording 1-4 cameras 100fps, 8 cameras 200fps, and 16 cameras 400fps

Video Output

Main monitor VGA (1024x768)

Audio

Recording and playback 1 channel (line mic and line out)
Connectors are 1/8" mini phone jacks

Alarm Inputs and Outputs

Number of inputs & outputs: 8 (non isolated for dry contact sensors & optional 16 I/O)
Connectors screwless & terminal blocks

Connectivity/Transmission

LAN / WAN 10/100 Ethernet card
Connector (LAN/WAN) RJ-45
Telephone jack RJ-11
Transmission Speed LAN : 120 Frame/Sec, PSTN : 1~5 Frame/Sec, ISDN : 3~10 Frame/Sec

Hardware

PC based, Windows XP™
Internal 200 GB hard disk drive (upgradeable to a total of 3 HD-with upgrade in Power Supply and IDE Card)
CDRW & 1.44 MB floppy drive
Pentium IV up to 3GHz, 512 MB RAM, 128 MB Graphic Card

Electrical

Power source 115-120 VAC; 50-60 HZ switchable, maximum 350W

Mechanical

Rack mount design
Black steel case

Environmental

Dimensions are 440mm wide x 452 mm deep x 175 mm high or (17.32"x17.8"x6.89")
Approx. weight is 40lbs or 18.18 kg
Operating Temperature is 5° to 40°C, 41° to 104°F
Operating Humidity below 90% RH

Warranty

1year for hard drive & labor

Video Standards

PAL/CCIR is standard



Key Features and Benefits

- 1-16 video channel inputs
- Simultaneous recording and playback
- Digital watermark
- Printer hardcopy/JPEG/BMP to diskette
- Web security ready
- Event log file function
- 'Video Loss' or 'No Video Alarm' when camera(s) off will control the relay output (Optional)
- Backup remotely via static IP or LAN
- PAN/TILT Zoom Control (Optional)

