

VC-3050D

สำหรับกล้องวงจรปิดที่สามารถปรับหมุนซ้าย-ขวา

FEATURES

- Heavy-duty permanent magnet synchronous motors, equipped with motor off-power protection, wind-driven resisted
- High performance, long-life gear drives, equipping two side IR illuminators is optional
- Auto-Scan with limit switches
- Die-cast aluminum construction, weather proof
- Model H supplied with internal heater for use in cold area



SPECIFICATIONS

Model	VC-3050D
Input voltage	AC 24V 50Hz
Current	AC 24V less than and equal to 1.2A AC220V less than and equal to 0.2A
Type of load	Top load
Max. Load	17 kg(37.4 lb)
Travels	Pan: 0 - 350 deg.
	Tilt: +10 - -60 deg.
Limit switches	Pan/Tilt adjustment
Speed	Pan: more than and equal to 1.2 deg./S
	Tilt: more than and equal to 4.5 deg./S
Model H heater power	30W/24V , 50W/220V
Transmission mode	Gear decelerate drive
Valid torsion	60NM
Operating Temperature	Without Heater: -20 - 55 deg. C(-4 - 131 deg. F)
	(Model H) With Heater: -45 - 55 deg.C (-49 - 131 deg.F)
Construction	Aluminum
Circumstance Standard	IP66
Relative humidity	98%
Weight	8.1 kg (17.82 lb)