

VC-3060

สำหรับกล้องวงจรปิดที่สามารถปรับมุมซ้าย-ขวา

FEATURES

- Compact and attractive appearance. Patent designed arranging wires can reduce. Length of wires, the wires and avoid damaging and fattig
- Heavy-duty permanent magnet synchronous motors, equipped with motor stall protection, wind-drift prevention, providing smooth and reliable operation
- High performance, long-life imported gear drives, optional equipped with two LR illuminators
- Specific outer shell is convenient for removal, installation and maintenance
- Auto-scan with limit switches. Die-cast aluminum construction, weather sealed
- Model H supplied with internal heater for use in high cold area



SPECIFICATIONS

Model	VC-3060
Input voltage	AC 24V/AC220/ 50Hz
Current	AC 24V less than and equal to 1.2A AC220V less than and equal to 0.2A
Max. Load	17 kg (37.4 lb)
Travels	Pan: 0 - 355 deg. Tilt : +10 - 90 deg. (Factory : +10- (- 60) deg.)
Speed	Pan: 9 deg./S Tilt: 4 deg./S
Model H heater power	30W /24V/220V)
Transmission mode	Gear decelerate drive
Type of load	Top load
Valid torsion	60NM
Operating Temperature	Without Heater: -20 - 55 deg. C (-4 - 131 deg. F) (Model H) With Heater: -45 - 55 deg.C (-49 - 131 deg.F)
Construction	Aluminum
Circumstance Standard	IP66
Relative humidity	98%
Weight	9.5 kg (20.9 lb)
Dimensions	214*289*290