

VC-3939W

สำหรับกล้องวงจรปิดที่สามารถปรับหมุนซ้าย-ขวา

FEATURES

- All connections made at the input connector, eliminating wire cut possibility
- Attractive appearance, constructed with ABS Plastic, meets most Fire resisting Requirements
- Square or round mounting plates equipped, no need for other mounts



Switzerland SAIA motors and gear drives, providing smooth and reliable operation for over 10,000 hrs under environment of 60 deg. C

SPECIFICATIONS

Model	VC-3939W
Input voltage	AC 24V AC 220V 50/60 Hz
Input power	10 VA
Connector	Two sets of 16 screw connection points on one board
Travels	Pan: 0 deg. - 350 deg.
	Tilt: +10 deg. - 60 deg.
Limit switches	Adjustment
Max. capacity	2.5 kg(5.5 lb)
Motor gear	Copper
Speed	Pan: more than and equal to 5.3 deg. /S
	Tilt: equal to 2.8 deg./S
Virtual torsion	Pan: 18.8 kg.cm (41.36 lb)
	Tilt: 26.8 kg.cm(58.96 lb)
Invert Mode	Pan instantaneous invert (by invert switch)
Load change	Pan: continuous Tilt: intermittence
Operation temperature	0 - 60 deg. C(32 - 140 deg. F)
Weight	W:1.08kg(2.38 lb)
	C:1.25kg(2.75 lb)
Dimensions	Products fixing means and sketch map
Construction	ABS Plastic