

## B/W CCD CAMERA

กล้องวงจรปิดชนิด ขาว-ดำ



Rear Panel

Model No : VC-512D, VC-513D, VC-523D

SPECIFICATION	VC-512D	VC-513D	VC-523D
Image Sensor:	1/3" LG CCD	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD
Effective Pixels:	CCIR: 500(H)x580(V) EIA: 510(H) x492(V)	CCIR: 500(H)x582(V) EIA: 510(H) x492(V)	CCIR: 752(H)x582(V) EIA: 768(H) x494(V)
Sensing Area:	4.9mmx3.7mm	4.9mmx3.7mm	4.9mmx3.7mm
Signal System:	CCIR/EIA	CCIR/EIA	CCIR/EIA
Horizontal Resolution:	<b>420 TV Line</b>	<b>420 TV Line</b>	<b>600 TV Line</b>
Lens Mount:	CS/C Mount (C Mount adapter option)	CS/C Mount (C Mount adapter option)	CS/C Mount (C Mount adapter option)
Backlight Compensation:	--	ON/OFF switchable	ON/OFF switchable
Electronic Shutter:	ON/OFF switchable	ON/OFF switchable	ON/OFF switchable
Shutter Speed:	1/50(1/60)-1/100,000 sec	1/50(1/60)-1/100,000 sec	1/50(1/60)-1/100,000 sec
Auto Iris Lens:	VIDEO	VIDEO/DC switchable	VIDEO/DC switchable
S/N Ratio:	more than 48db	more than 48db	more than 48db
Minimum Illumination:	<b>0.2Lux /F12</b>	<b>0.05Lux /F12</b>	<b>0.1Lux /F12</b>
Video Output:	1.0Vp-p, 75Ω	1.0Vp-p, 75Ω	1.0Vp-p, 75Ω
Power Requirement:	DC12V	DC12V	DC12V
Power Consumption:	Less than 1.8W	Less than 1.8W	Less than 1.8W
Video Out:	BNC	BNC	BNC
Dimensions:	58mmx50mmx115mm	58mmx50mmx115mm	58mmx50mmx115mm