

VC-5209H

กล่องกันน้ำ สำหรับกล้องวงจรปิดที่สามารถปรับหมุนซ้าย-ขวา

- Environmental sealed, Pan/Tilt installed
- Available pendant or wall mounts
- Weatherproof of DMC Back Box
- Auto heating system available for cold area application: ON at 10 deg. C add to 5 deg. C(50 deg. F add to 41 deg. F) and OFF at 0 deg. C±5 deg. C(68 deg. F add to 41 deg. F)
- Swiss SAIA motor are optional, providing smooth and reliable operation
- VC2700 wall mounts are recommended



SPECIFICATIONS

SPECIFICATIONS	
Model	VC-5209H
Voltage	AC 24V 50/60HZ
Power	Pan/Tilt: motor:10 W Heater/Blower:36W
Travel	Pan : 0 - 355 deg. Tilt : 0- 90 deg.
Speed	Pan : 12 deg./S Tilt : 12 deg./S(YA5109) Pan : 24 deg./S Tilt : 12 deg./S
Limit switch	Pan/Tilt adjustments
Max.size for camera+lens (L*W*H)	230*80*75mm (9.06"*3.15"*2.95")
Heating Activation	Heater : ON 10°C±5°C (50±41°F) OFF 20°C±5°C (68±41°F)
Weight	5.3kg(11.66 lb)
Operating Temperature	-5 deg.C--60 deg.C(23 deg.F-140 deg.F) Model H : -25 deg.C - 60 deg.C(-13 deg.F-140 deg.F)
Material	Back box: DMC Lower Dome: Acrylic P/T Assembly: Aluminum